

*Halogen Free*

NOTES:  
1.MATERIAL:  
1-1:HOUSING:PA10T+35%GF(VICNYL R635NH);UL 94V-0,  
COLOR:BLACK  
1-2:TERMINAL:PHOSPHOR BRONZE(C5210R-EH);T=0.25mm  
TREATMENT:  
1.GOLD FLASH ON CONTACT AREA,MATTE SN 50u" MIN  
ON SOLDER TAIL,ALL OVER NI 50u" MIN.  
2.GOLD 30u" MIN ON CONTACT AREA,MATTE SN 50u" MIN  
ON SOLDER TAIL,ALL OVER NI 50u" MIN.  
1-3:SHELL:SUS(201);T=0.20mm,TREATMENT:50u" NI  
1-4:LED:WHITE/AMBER,TREATMENT:TIN  
1-5:MYLAR:THERMAL PLASTIC;COLOR:YELLOW  
2.SPECIFICATIONS:  
2-1.VOLTAGE RATING:150VAC MAX.  
2-2.CURRENT RATING:1.5AMP MAX.  
2-3.INSULATION RESISTANCE:1000MΩ MIN. AT 500V DC.  
2-4.DIELECTRIC WITHSTANDING VOLTAGE:  
500V AC 60HZ 1MINUTE.  
2-5.DURABILITY:5000 CYCLES.  
2-6.OPERATING TEMPERATURE:-30°C TQ+70°C.