



項次	名稱	料號	材質	電鍍或顏色	數量	備註
1	母膠心	UA0017000	NYLON66,UL 94 V-0	BEIGE	1	
2	本體護蓋	UA00570XX	BRASS,T=0.40±0.03MM	TIN OR NICKEL PLATED	1	
3	焊線端子	UA00340XX	PHOSPHOR BRONZE T=0.25±0.03MM	SEE TABLE	4	
4	母座-後塞	UA0018000-1	PBT+15%GF,UL 94 V-0	BLACK OR WHITE OR BEIGE	1	BA

ELECTRICAL CHARACTERISTICS:  
 RATING:30V DC/AC 1A Max.  
 CONTACT RESISTANCE:30mΩ Max.  
 INSULATION RESISTANCE:100MΩ Min.at 500V DC.  
 DIELECTRIC STRENGTH:750V AC/1 minute.  
 INSERTION FORCE: 3.6kgf MAX  
 WITHDRAWAL FORCE: 1.0kgf MIN

TABLE:

XX	電鍍
11	G.F./TIN PLATED前金後錫
12	3U" G./TIN PLATED前金後錫
13	5U" G./TIN PLATED前金後錫
14	10u" G./TIN PLATED前金後錫
15	15U" G./TIN PLATED前金後錫
16	20U" G./TIN PLATED前金後錫
17	30U" G./TIN PLATED前金後錫
18	50U" G./TIN PLATED前金後錫

**東莞世華電子有限公司**  
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)  
 地址:東莞市塘廈鎮諸佛嶺178工業區  
 TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY	ITEM	USB CONNECTOR(series A)	ANGLE PROJECTION	UNIT	MM		
CHECKED BY		-母座(有腳180°)		SCALE	4:1	BA	材質變更,舊圖作廢 04/07/2003
APPROVED BY	PART NO	UA09200XX	TOLERANCE	X.XX±0.20	DATE	04/07/2003	REVISION
							DESCRIPTION
							DATE